



AF506

Pneumatic Brad Nailer

Slim Contact Tip Design

For Precise Woodworking Fastening Applications



Lightweight:

1.3 kg

Complied with EN ISO11148-13

- **Contact arm stroke:** more than 5mm
- **Contact arm spring loading:** more than 60% of machine weight

Multidirectional exhaust port



Driving depth adjustment with dial



Slim nose tip allows easy access to a desired fastening point



Remaining nail view window



Tool-less Quick Release Cam-Lock opens nail guide assembly to clear jammed nails



Soft grip with ribs

Air duster blows away dust and chips from workpiece by pushing a button



Reversible belt hook can be attached to the left or right side of tool



SPECIFICATIONS

Pneumatic Brad Nailer

AF506

Capacity	Length: 15 - 50 mm (5/8" - 2") Gauge: 18 Ga
Operating Pressure	0.49 - 0.83 MPa (70 - 120 PSI)
Magazine Capacity	100
Dimensions (L x W x H)	250x70x256mm
Net weight	1.3 kg

Standard Equipment: Safety Goggles, Oil Supply, Nose Adapter.




Depth Adjustment



Carrying Case

Accessories

Brad Nails	Length	Part No.
Brad Nail (5,000 pcs/box)	15mm	B-04307
	20mm	B-04313
	25mm	B-04329
	30mm	B-04335
	35mm	B-04357
	40mm	B-04379
	45mm	B-04385
	50mm	B-04391



Length



Makita

Makita Gulf FZE

www.makita.ae