

CF003G Cordless Fan D 4 Powered by 40V MAX XGT Li-ion Battery / 18V LXT Li-ion Battery / AC

Thakita

## 450mm FAN DIAMETER

A powerful motor that delivers high airflow up to 130 m<sup>3</sup>/min

## **COMPATIBLE WITH THREE POWER SOURCE MODE**









Front fan cover has been redesigned to supply air widely around the appliance therefore, this model is suited for air blowing or ventilation in a large places such as factories, warehouses, etc

Max Air<br/>Flow VolumeMax Air Speed<br/>(Measured at 1 m away<br/>from the appliance)Runtime<br/>(with 40V max XGT<br/>8.0Ah battery)1200<br/>m³/min3000<br/>m/min2200<br/>min (with oscillation)



Stepless air flow volume setting	Automatic Oscillation	Manual angle adjustment of fan head	Three stages automatic timer	Foldable Carrying Handle	Mounted onto MAKPAC cart	Accessory Case
Dial-style air flow volume adjustment (38 - 120m <sup>3</sup> /min)	Automatic oscillation angle adjustment: 60°, 90°, 120° left/right		1 hour, 2 hours, 6 hours	For easy transportation	Portability can be enhanced by mounting the appliance onto MAKPAC cart	Located on the front of the appliance for storing AC adapter & battery
SPECIFICATIONS	96-30	0 m/min				

Air velocity	96-300 m/min
Air flow	38-120 m³/min
Fan diameter	450 mm
Fan head angle adjustment	Up: 90° / Down: 45° / Left: 90° / Right: 90°
Automatic oscillation	Left: 60, 90, 120° / Right: 60, 90, 120°
Continuous use (with oscillation)	220 minutes (with 40V max XGT 8.0Ah)
Continuous use (with oscillation)	85 minutes (with 18V LXT 6.0Ah)
Dimensions (L x W x H)	312 x 633 x 770 mm (without battery)
Net weight	7.9 kg (without battery)
Standard Equipment: AC Adapter.	



VARIANTS	Battery	Charger	Carry Case
CF003G Z	NO	NO	NO



MAKITA GULF FZE