DF001GXGT - Cordless 13mm Driver Drill





Excellent performance in continuous heavy duty applications

Delivers **140Nm** of Max torque achieved with combination of high power brushless motor and innovative XGT battery

New electronic clutch settings

A higher range of torque can be covered than with mechanical clutch

- 41-stage setting in gear one
- 21-stage setting in gear two

XGT: Electronic Clutch Easy jog dial LXT: Mechanical Clutch fa



Digital display

Active Feedback sensing Technology

Active Feedback Sensing Technology (AFT) that turns off the motor if the rotation speed suddenly slows down.





Compact overall length

For easy handling and control



Efficient, Durable, Compact, Lightweight and Outstanding Performance Driver Drill

A powerful, brushless Driver Drill for screwdriving and drilling with two different power settings for professional use. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. A combination of innovative tool design and higher output batteries, providing a durable solution for the professional user with high demand



| Capacity | Steel: 20 mm | |
|----------------------|---------------------------------|--|
| | Wood (Auger-Bit): 50 mm | |
| | Wood (Self-Feed Bit): 76 mm | |
| | Wood (Hole Saw): 152 mm | |
| Chuck Capacity | 1.5 - 13 mm | |
| No Load Speed (RPM) | High / Low: 0 - 2,600 / 0 - 650 | |
| Max Fastening Torque | Hard / Soft: 140 / 68 N·m | |
| Max lock torque | 125 Nm | |

Sound Pressure Level 75 dB(A)
Dimensions (L x W x H) 181x86x282 mm

Net weight 3.0 kg

| AWOL | a h | Jariante |
|------|-----|-----------------|
| Aval | au | Variants |

| ТҮРЕ | VARIANTS | BATTERIES | CHARGER | MAKPAC CASE | | |
|---------------------------|-----------|------------------------|---------------|-------------|--|--|
| W/O Battery / Charger | DF001G Z | - | - | - | | |
| With Battery / Charger | DF001G M2 | BL4040 (4.0Ah) 2pcs | DC40RA 1pc | Type 3 | | |
| | | | | | | |

