

# **DFR551**

# **Cordless Auto Feed Screwdriver** Powered by 18V LXT Li-ion battery

# High Rotation Speed 6,000 rpm



MINION LXT BL XPT





#### **Push Drive Technology**

The motor rotates at full speed only when the screw is pressed against the board to reduce power consumption and noise



**PUSH** 



DRIVE Motor stops





## **More Reliable Casing Attachment**

#### **Enhanced durability**

- · Screw feeding mechanism redesigned to improve durability and reduce screw fall
- High durability aluminium casing



#### Quick attachment / removal

Autofeed housing is designed with a screwless one-touch hook for effortless attachment and removal



### **Unfastening Operation**

The tool allows you to change the direction of driver bit rotation with ease, either towards the right (clockwise) to tighten a screw or towards the left (counterclockwise) to loosen a screw.





SPECIFICATIONS	
Screw Strip	3.5 - 4.2ø x 25 - 55mm
Driving Shank (Hex)	6.35 mm
No Load Speed (RPM)	0 - 6,000
Sound Pressure Level	74 dB(A)
Vibration Level	Screwdriving w/o Impact: 2.5 m/s² or less
Dimensions (L x W x H)	396 x 88 x 165 mm (without battery)
	396 x 88 x 211 mm (with BL1860B)
Net weight	1.5 kg (without battery)
Standard Equipment: Belt Clip.	

Variants	Model #	Battery	Charger	Carry Case
BARE TOOL	DFR551ZJ	NO	NO	MAKPAC

# **ACCESSORIES**

Wariable Speed

#### Casing set (standard) Part No. 191W94-5



Reversing

## Bits (5pcs/set) (optional)

Description	Qty	Part No.
Phillips Bit 2-155 set	5	191V02-0
Square Bit 2-155 set	5	191V04-6
Pozidrive Bit 2-155 set	5	191V06-2



## Available drywall screw strip (optional)

•		
Description	Qty	Part No.
ø3.9 x 41	1,000	P-04139
ø4.0 x 32	1,000	A-12413
ø4.0 x 40	1,000	A-12429



