

DHG181 CORDLESS HEAT GUN Powered by 18V LXT Li-ion battery

MAX. 550°C AIR TEMPERATURE



For Various Applications









Quick release mechanism for easy Nozzle replacement

Nozzle can be removed without touching the hot metal part simply by turning Plastic ring. Compatible with current nozzles for AC machines



Air volume setting

The air volume is switchable by sliding the air volume switch to: Stage 1: 120 L/min, Stage 2: 200 L/min



Single LED job light

with after-glow function





Lock-on button

switch





Air temperature adjustment dial

Stepless adjustment for setting to suitable temperature for your application



Continuous Runtime

Low Mode

 $30_{\rm mins}$

High Mode

With BL1860B battery

WIDE VARIETY OF ACCESSORIES

Glass protection nozzle (Standard Equipment)

Solder sleeves reflector

(Optional Accessory)
For shrinking tube

Part No. PR00000033

Part No. PR0000028



For shrink wrapping Part No. PR00000029

Welding nozzle

Part No. PR00000034

■D Built-in Job Light

Wide-slot nozzle



tube

Part No

PR00000030

Reflector nozzle

For bending plastic

Pressure roller (Optional Accessory)
For holding a hot sheet and



the surface of the sheet Part No. PR00000031

Reduction nozzle 20

(Standard Equipment)

For welding sheet from





Overlap welding nozzle












| SPECIFICATIONS |
|---------------------------|
| Air Temperature (6 stages |

Electronic 2-Speed

Dial 1/ 2/ 3/ 4/ 5/ 6: Ambient temperature/150/ 250/ 350/ 450/ 550°C s by dial) Air Flow Stage 1: 120 L/min, Stage 2: 200 L/min Continuous run time 21 mins (on a full battery charge of BL1860B) Dimensions (L x W x H) 173 x 79 x 255 mm (with BL1860B) Net weight 1.4 kg





| Variants | Battery | Charger | Carry Case |
|----------|-------------------------------------|-------------|------------|
| DHG181RT | 1pc of 18V LXT Li-ion 5.0Ah battery | 1pc Charger | YES |
| DHG181ZK | NO | NO | YES |

