

DHP489 (13mm) (1/2") **Cordless Percussion Driver Drill** Powered By 18V LXT Li-ion Battery

# **EXCELLENT DRILLING CAPACITY**

**Maximum Drilling Capacity** for masonry work is 16mm

**Brushless Motor delivers** 

73 N.m Max Fastening Torque (Hard)

**Compact & Slim Design** 175mm



Light Weight

1.84 kg (Without Battery)

3 Modes for various applications



Drilling Mode

> Screwdriver Mode

Hammering Mode



makita







### **Robust Keyless Drill Chuck**

with single metal sleeve

Twin LED Job Light with preglow and after glow functions



#### Variable Speed Control by trigger switch







Tnakita.

makitå

5000 (18V

111

#### **Aluminum Gear Housing**

Robustness is highlighted by the aluminum diecast cover added around the gear housing case

#### **Belt Clip**

#### **Excellent Maneuverability**

Despite increased efficiency, the overall length is very short due to optimally redesigned gear assembly



#### **Extreme Protection Technology (XPT)**

is engineered for improved dust and water resistance for operation in harsh conditions



## SPECIFICATIONS

Capacity	Masonry: 16 mm; Steel: 13 mm; Wood (Self-feed bit): 51 mm			
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")			
Impacts per minute (IPM)	High: 0 - 27,000 / Low: 0 - 8,250			
No Load Speed (RPM)	High: 0 - 1,800 / Low: 0 - 550			
Max fastening torque	Hard: 73 N·m (650 in.lbs.)			
	Soft: 40 N·m (350 in.lbs.)			
Max lock torque	80 N·m (700 in.lbs.)			
Sound pressure level	81 dB (A)			
Sound power level	92 dB (A)			
Vibration level	Work mode: impact drilling into concrete: 9.5 m/s <sup>2</sup>			
Dimensions (L x W x H)	175 x 81 x 261 mm (with BL1860B)			
Net weight	1.84 kg (without battery)			
Standard Equipment: (+)(-) Bit, Belt Clip.				
🌃 Variable Speed 💮 Brake	Reversing K2 Mechanical 2-Speed			
Keyless Chuck 🕅 Torque Se	etting 21 ED Built-in Job Light			



Variants	Battery	Charger	MAKPAC Carry Case
DHP489 RTJ	2pcs of 18V LXT Li-ion 5.0Ah batteries	lpc Charger	YES
DHP489 Z	NO	NO	NO



