



**DJV186 Cordless JIGSAW**  
Powered by 18V LXT Li-ion battery

**LIGHTWEIGHT CONSTRUCTION, ERGONOMIC DESIGN AND**  
with versatile cutting performance

Capable of cutting various materials including wood, aluminium  
and mild steel

**18mm**  
STROKE LENGTH

**2,900 SPM**  
STROKE PER MINUTE



The comfortable grip and balanced design ensure better control, perfect for both small detailed cuts and long straight cuts



Adapt to all 18V LXT batteries including LXT basic battery



Please Note:- Charge the LXT batteries with the LXT battery chargers

Charge the LXT BASIC battery with the LXT BASIC battery charger

Variable speed control by trigger  
Makes it easier to align with cutting lines.




**Built-in blower function**  
Clears dust and debris from the cutting line for better visibility during operation



**Connectable to a vacuum cleaner**  
for dust collection



**Change lever for 3 orbital settings and straight cutting**  
with a simple turn of the lever



**Rigid aluminum base**  
Tilts 0° to 45° left and right

SPECIFICATIONS	
Stroke length	18 mm
Strokes per minute	0 - 2,900 min <sup>-1</sup>
Capacity	Wood: 65 mm   Mild steel: 6 mm Aluminum: 10 mm
Bevel range	0 - 45 °
Vibration level	Cutting boards: 7.5 m/s <sup>2</sup> , Cutting sheet metal: 4.2 m/s <sup>2</sup>
Sound pressure level	85 dB(A)
Dimensions (L x W x H)	241 - 257 x 81 x 196 mm
Net weight	1.5 kg (without battery)

VARIANTS	BATTERY	CHARGER	CASE	UPC CODE	PRICE
DJV186 WVE	2pcs of 18V (2.0Ah) LXT Basic battery BLB182	1pc LXT Basic Charger DCB18WA	PLASTIC CASE	197050 01182 4	
DJV186 Z	NO	NO	CARTON	197050 01185 5	

- Variable Speed
- Brake
- Orbital Cutting
- Bayonet Shank Jig Saw Blade
- Dust Collection

### OPTIONAL ATTACHMENTS

**Guide rail set**  
3m: 194367-7  
1.4m: 194368-5



**Guide rail adapter set**  
For use with guide rail 198704-7



**Push clamp set**  
To hold guide rail 1913K5-7



**Position sheet**  
423360-7



**Support base set**  
1915R3-2  
Reduces unstable tilting of the blade during bevel cuts, enabling stable cutting

Enhances the precision of curved cuts



**Guide rule set**  
192732-4



**MAKITA GULF FZE**

www.makita.ae |

MAKITA TOOLS EDITION # 684