



DML810


Cordless Area Worklight



Max 5,500 lm Self-Righting Area Light

For dim-lit areas and work sites, where portability is a pre-requisite

Powered by both



and



Self-righting design



Light diffusing lens

able to soften the light of LED and to provide widespread illumination



Inlet type AC power supply cord

Detachable and can be stored compactly on the back of the light body when not in use



Reflector

glows in the dark to help you locate the worklight body



Padlock hole

for battery theft protection*
*Padlock not included

Color temperature of approx 5,000K provides daylight white light, which is similar to the natural light and ideal for working spaces



Self-righting design



Switch



3-stage brightness switch
ON/OFF Power Switch
Adjustable illumination area switch

3-stage brightness switch



Low: 1,500lm
18h

Med: 3,000lm
8.5h

Hi: 5,500lm
4.0h

Continuous run time
(BL1860B x 2)

Adjustable illumination area



Left: 180°

360°

Right: 180°

Controller with memory function remembers the brightness setting and the lighting area setting last time you power off, allowing the user to avoid adjusting again.

Powered by both DC and AC

DC



AC



IP54

certified dust and water resistance
(only with DC power)

Carrying handle



having openings through which anti-theft chain or cable can pass



AC outlet for connecting multiple units together

- Up to 8 units can be connected together
- Equipped with a circuit breaker for protection from overload



Battery capacity warning function

automatically notifies about reduction in battery capacity with the decrease of illuminance
(Only four LEDs are on for notification)



Specification

Run Time (hrs)	High: 4.0 / Medium: 8.5 / Low: 18 (with BL1860B x 2)
Illuminance	at 1m from the light source: 550 / 300 / 150 lx
(High / Med / Low)	at 3m from the light source: 70 / 40 / 20 lx
	at 5m from the light source: 25 / 15 / 7 lx
Luminous Flux	High / Med / Low: 5,500 / 3,000 / 1,500 lm
Dimensions (L x W x H)	420x420x787 mm
Net weight	15.3 kg

Standard Equipment: AC Power Cord.
(subject to change)

Available Variants

AMPERE	VARIANTS	BATTERIES	CHARGER	CARRY CASE
Without BATTERY and CHARGER	DML810Z	0	0	NO



Makita Gulf FZE

www.makita.ae