

DPB182

Durable Aluminium Frame



Stable cutting with highly rigid aluminium structure



Frame improves rigidity and prevents blade from coming off.

Prevents blade slipping on wheel by raising tension force **Hook** (option) for hanging on the guard rail of suspended or supported scaffolds







Single LED job light with pre-glow function



Easy blade replacement by quick blade tension lever



Easy blade track adjustment simply by turning the screw



Adjustable stopper plate convenient to cut pipes near wall, floor and ceiling



OPTIONAL ACCESSORIES (available in our range)

Bi-Metal Band Saw Blade						
(5pcs./ set) Wave teeth						
Width : 13 mm						
Thickness : 0.5 mm						
Length : 835 mm						
No. of teeth inch	Thickness of work piece	Application	Part No.			
14	3-6mm	Plastics and non-ferrous	B-40543			
18	2-3mm	metal. Mild steel, cast	B-40559			
24	Less than 2mm	steel and cast iron	B-40565			



SPECIFICATION	DPB182	DPB181 (OLD MODEL)	
Capacity	Round workpiece (dia) : 64mm	Round workpiece (dia) : 64mm	
	Rectangular workpiece	Rectangular workpiece	
	without stand : 64x64mm	without stand : 64x64mm	
Blade speed	3.2m/s	3.2m/s	
Dimensions (L x W x H)	477x197x229mm	468x197x233mm	
Net weight	4.0kg (with battery)	3.5kg (with battery)	
Housing material	Aluminium	Plastic	

Standard Equipments: Band saw blade, Hex wrench



Built-in Job Light

AVAILABLE VARIANTS							
ТҮРЕ	VARIANTS	BATTERIES / PCS	CHARGER	CARRY CASE			
WITHOUT BATTERY AND CHARGER	DPB182Z	0	NO	NO			



