

DPB183

18V LXT Li-ion Cordless Portable Band Saw



Easy installation / removal of blade

Redesigned structure of wheel cover and frame (lowered aluminum portion than wheel) for easy installation / removal of blade when the wheel cover is open





Stable cutting with highly rigid aluminum structure

- Rigid aluminum die-cast frame and gear housing prevents the blad from sliding off the wheel
- The rigidity also allows for increasing the tension on the blade to prevent the blade from slipping on the wheel



Variable speed control by trigger •

Variable speed control by dial

an optimum cutting speed can be selected to suit application





Catch bracket

protects the tool body from damage by hitting against workpiece



Easy blade track adjustment simply by turning the screw





Brushless Motor and Constant Speed Control minimizes the reduction in blade speed to provide stable cutting



Compact design

Drastically reduced size has been achieved by relocating the handle for easier operation even in tight spaces



ACCESSORIES

Band saw blade [Width: 13 mm, Thickness: 0.5 mm, Length: 835 mm]							
Part No.	Туре	Width (mm)	No. of teeth per inch	Teeth shape	Application		
B-40543		3mm-6 mm	14	Wave teeth	Plastics and non-ferrous metal.		
B-40559	Bi-Metal (5pc.)	2 mm- 3 mm	18	-	Mild steel, cast steel and cast iron.		
B-40565		less than 2mm	24		Hard steel and stainless steel.		

Grip 36 Complete

Part No. 158237-4



Cordless Por	table Band	Saw					
DPB183							
Capacity	Round: 66 mm;	Square: 66 x 66 mm					
Blade Speed	0 - 3.2 m/s						
Blade Size	Length: 835 mn	n					
	Width: 13 mm						
	Thickness: 0.5 n	nm					
Dimensions (L x W x H)	392x174x242 m	nm					
Net weight	3.9 kg						
Standard Equipment: Band Saw Blade, Hex Wrench, Hook, Grip .							
Wariable Speed	Marake Brake	Built-in Job Light					
Constant Speed	Carrying Case						

Туре	Variants	Batteries/pcs	Charger	Carry Case
W/o Battery and Charger. Comes in Plastic Carry Case	DPB183Z	0	NO	YES
	A A		THE RESERVE	
		A		1

