

LENGTH ADJUSTABLE TELESCOPIC SYSTEM HIGH SPEED CUTTING enables SMOOTH & EFFICIENT TRIMMING and LOW NOISE LEVEL Overall length ■ Slide-type front Max. 2,511 mm 1,889 mm grip position is adjustable for personal fit and Lock lever comfort maximum for tool-less easy work efficiency in adjustment of pole different working extension postures

NEW Chip receiver

can make it easier for user to collect leaf and twig debris, thanks to:


- lower height of the connecting hooks
- reduced step height of the edge of the chip catching plate



Angle adjustable hedge trimmer head

- 60° tilt-up to 75° tilt-down from the horizontal position • 10 angle settings
- 10 angle settings (60°, 45°, 30°, 15°, 0°, -15°, 30°, -45°, -60°, 75°)





eXtreme Protection Technology

Dust and drip-proof performance is enhanced for use in harsh environments



ACCESSORIES

Shear blade assembly Part No. 191P00-8











SPECIFICATIONS		
Blade Length	460 mm	
Max Cutting Capacity	18 mm	
Strokes Per Minute (SPM)	3,600	
Cycles Per Minute (CPM)	1,800	
Continuous Use (min.)	122 (w/ BL1850B)	
Vibration Level	2.5 m/s² or less	
Sound Pressure Level	74dB(A)	
Dimensions (L x W x H)	1,889 - 2,511 x 87 x 134 mm	
Net weight	3.3 kg	
Standard Equipment: Blade Co	ver, Chip Receiver, Shear Blade.	

Variants	Battery	Charger	Carry Case
DUN461WRF	1pc 18V, 3.0Ah	YES	NO
	Li-ion Battery		
DUN461WZ	NO	NO	NO

