

DUP180

Battery Powered Pruning Shear Powered by 18V LXT Lithium-ion Battery



MAX. CUTTING CAPACITY

ø**30**mm

ABOUT

8000 pcs* LIGHT WEIGHT

0.68kg

* When cutting ø15mm branches with BL1860B battery














SLIM AND LIGHT WEIGHT DESIGN

The use of BL Coreless motor* allows for reduction in the grip diameter and weight to reduce user's fatigue from pruning

*BL motor without iron core on which copper coil wire is wound



Standby Mode

To turn off the tool, pull and hold the switch trigger for more than 3 seconds to close the shear blades, then release the switch trigger, and then press the main power button

LED Indicator

Indicator Lamp

Power ON

Blinking: Battery capacity warning (when the capacity is 20% or less)

Solid on: Error indication (No battery capacity/

Thermal protection/ Overload)

Adjustment of blade overlap when closed

by pressing and holding Blade opening angle adjustment button for 3 seconds or more when fully closed



External Oil Port

The blades respond to the trigger with

sensitivity, ensuring a comfortable use experience

Lubrication oil can be injected without disassembling the blades



Select from four angles to match branch thickness



Blade opening angle adjustment button

Main Power Button

Thick Branch ø10_{mm}


ø**18**mm

ø25_{mm}

Thin Branch

Adapter Cord Length: 1.4m Part No. 630F23-0

ø**30**mm







STANDARD ACCESSORIES

Shear blade U Set Replacement upper blade for Pruning shears Part No. 1913P4-4



Shear blade L Set

Replacement lower blade for Pruning shears Part No. 1913P3-6



SPECIFICATIONS

Capacity	Max cutting: 30 mm	
Vibration level	2.5 m/s² or less	
Sound pressure level	70 dB(A) or less	
Dimensions (LxWxH)	296 x 40 x 99 mm	
Net weight	0.68 kg	

Dimensions and Net Weight values shown are without battery, battery adapter, harness and controller for operation)

Standard Equipment: Oil Spray, Hex Wrench, Socket Wrench, Dressing Stone, Holster.









Brake Anti-Restart S Torqu	ıe Limiter			
VARIANTS	Battery	Charger	Carry Case	
DUP180 Z	NO	NO	NO	





