

Threaded Shaft

Mixer run time 25 min

Blade 165mm
Battery: BL1850B
Material: One liquid paint 4L
Rotation mode: HI speed mode



Battery cover protects battery from any splashing







For a wide range of applications

Mechanical 2-speed (0-350 & 0-1,300RPM)



Rear Handle with Soft Rubber Grip ergonomically designed for comfortable operation

ACCESSORIES

Shaft	Stainless Steel						
Part No.		A-43751*					
Mixing Blade	165	150	130	135			
Application	for m	for mixing high viscosity materials like plaster, mortar					
Shape			(0)				
Bolt sold separate	V		V	73 (- 7			
Part No.	A-43692*	A-43686	A-43670	A-43723			
Bolt Size	M8 x 18	M8 x 25	M8 x 18	W5/16 x 16			
Part No.	265220-5*	251686-5	265220-5*	265475-2			

SPECIFICATION						
Blade Diameter	165 mm (6-1/2")					
No Load Speed (RPM)	High / Low: 0 - 1,300 / 0 - 350					
Max Output	650 W					
Vibration Level	Operation w/o Load: 2.5 m/s ² or less					
Sound Pressure Level	74 dB(A)					
Dimensions (L x W x H)	w/ Mixing Blade: 916x89x231 mm					
	w/o Mixing Blade: 320x89x231 mm					
Net weight	2.5 - 2.8 kg					
Standard Equipment: Mixing blade 165, Shaft complete, Shaft holder, Grip,						
Front cover, Tote bag, Wrenches.						
▼ Variable Speed ▼ Mechanical 2-Speed ► Soft Start						

AVAILABLE VARIANTS							
ТУРЕ	VARIANTS	BATTERIES / PCS	CHARGER	MAKPAC CASE			
With 2pcs 5.0Ah batteries & 1pc Charger	DUT130RTE	2	YES	NO			
Without battery and Charger	DUT130Z	0	NO	NO			

