

EA6100P PETROL CHAIN SAW 50cm (20")

The Perfect All-Round Chain Saw



With SAS-Technology

Reduction of operating cost by up to 20% less fuel consumption and low emissions for environmental and user benefit

Intake air pre-cleaning • significantly reduce dirt particles at an early stage

 SafetyMatic chain brake to stop the chain instantly in case of kickback

> Lateral chain tensioning provides easy operator access

Metal spike bar as standard for cutting logs to length

desirabilità desirabilità de la constantia de la constantia de la constantia de la constantia de la constantia

Steel spring damping

Vibration damping with oil and fuel resistant steel springs for user's comfort and health Solid bar studs

for a long-lasting firm hold of the guide bar



EasyStart Spring assisted starter combined with optimized engine management signitificantly reduces

resistance



0 19

Touch&Stop one lever control with clearly defined positions for cold starting, operation and



Primer pump for easy cold start



Extended worktime with Longlife Filter system Tool-less change and easy cleaning



External sprocket For simple, uncomplicated chain installation



Big 0.8 L fuel tank Up to 30 minutes operating with one tankfill



One-piece hood for easy maintenance



Optimum chip exhaust for avoiding jams

SPECIFICATION			
Guide bar length	500mm (20")		
Saw chain	Pitch: 0.325 (3/8")		
A /1	Gauge: 1.5 mm (0.058")		
Displace ment	60.7 mL		
Engine power	3.4 kW		
Fuel Tank Capacity	0.8 L		
Chain Oil Tank Volume	0.48 L		
Sound Pressure Level	105 dB(A)		
Sound Power Level	117 dB(A)		
Vibration Level <mark>Front Gri</mark> p	5.0 m/s ²		
Vibration Level Rear Grip	4.0 m/s ²		
Dimensions (L x W x H)	435 x 243 x 312 mm		
Power head weight	6.0 kg		




Standard Equipments: Saw Chain, Guide Bar, Guide Bar Cover, Socket Wrench, Hex Wrench, Screwdriver



Primer Pump

Anti Vibration







Chain Brake



Rapid Start



Capacitor Discharge Ignition

ACCESSORIES									
	Guide Bar	Saw Chain							
Bar length	Part No.	No. of drive links	Gauge	Pitch	Cutter Type	Part No.	Part No.		
50cm / 20"	445050651	72	1.5mm / 0.058"	3/8"	73LP / FC	528099772	952020650		



