



AC ANGLE GRINDERS (WITH PADDLE SWITCH TRIGGER)

GA4050 (100MM) | GA4550 (115MM) | GA4550R (115MM) | GA5050 (125MM) | GA5050R (125MM)

POWERFUL 1,300W MOTOR

WITH PADDLE SWITCH TRIGGER

ANGLE OF SIDE GRIP TO GEAR HOUSING: 110°



	100mm	115mm	125mm
GA4050		GA4550	GA5050
		GA4550R	GA5050R




Easy-to-operate large paddle switch trigger

works properly wherever the user holds the barrel grip



High durability

More durable in cutting and grinding, due to longer service life of motor, carbon brushes, etc



Enhanced shaft locking mechanism

- Gear housing is redesigned to prevent breakage of the shaft locking mechanism.
- Large size lock pin cap allows for normal shaft locking operation even with a thick-gloved finger



Anti-drop holders

allows to attach anti-drop strap, etc.



Machined bevel gears

High continuous rating input

By using new Type 55-55 motor, these grinders have high continuous rating input and easy-to-hold slim barrel grip that are similar to competitor models

Easy-to-hold

provides less hand fatigue and more control of the machine due to:

- Grip circumference smaller than 9564P series
- Ergonomic design

Angle of side grip to gear housing



With soft start

GA4550R/ GA5050R

minimizes start-up shock and makes the tool start smoothly

With anti-restart function

GA4550R/ GA5050R

minimizes accidental start-up even if the tool is plugged to power source with the switch "ON".

Tool-less wheel cover (Slide lever style)

allows for fast and easy angle adjustment and installation/removal of wheel cover



Model No.	Wheel Size			Angle of side grip to gear housing	Soft Start	Anti-Restart Function
	100mm	115mm	125mm			
	GA4550	GA4550	GA5050			
-	GA4550R	GA5050R	✓	✓		

SPECIFICATIONS	GA4050	GA4550 / GA4550R	GA5050 / GA5050R
Continuous rating input	1,300W	1,300W	1,300W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
No Load Speed (RPM)	11,000	11,000	11,000
Vibration Level	Surface Grinding: 6.5 m/s ²	Surface Grinding: 7.0 m/s ²	Surface Grinding: 7.5 m/s ²
(Normal side grip)	Disc Sanding: 2.5 m/s ²	Disc Sanding: 2.5 m/s ²	Disc Sanding: 2.5 m/s ² or less
Anti-restart function	-	only in GA4550R	only in GA5050R
Soft Start	-	only in GA4550R	only in GA5050R
Dimensions (L x W x H)	325x117x110 mm	325x130x117 mm	325x140x117 mm
Net weight	2.3-2.6 kg	2.4-2.8 kg	2.5-2.8 kg
Power supply cord	2.5 m	2.5 m	2.5 m

Standard Equipment: Side Grip, Lock Nut Wrench

   [Soft Start only in GA4550R and GA5050R]



Makita[®]
Makita Gulf FZE
www.makita.ae