

# GA7070 (180mm) / GA9070 (230mm)

Large Angle Grinders (Straight Handle type)

# 2,800W POWER

WITH MECHANICAL BRAKE, AFT FUNCTION and CONSTANT SPEED CONTROL





**Rotatable Main Handle** can be positioned to suit most cutting and grinding operations



#### **Anti-restart function**

prevents accidental startup Even if plugged in with the switch at "ON" position, the tool does not start. At this time, the indication lamp blinks red and shows that the unintentional restart proof device is functioning



### **ACCESSORIES**

## **Dust Collecting Wheel Guard**

For Diamond Cutting Wheel Part No. 198514-2 (GA7070) Max cutting depth: 35mm Part No. 198440-5 (GA9070) Max cutting depth: 60mm





| SPECIFICATIONS                  | GA7070   | GA9070   |
|---------------------------------|--|--|
| Continuous Rating Input         | 2,800W (127V : 2200W)  | 2,800W (127V : 2200W)                                  |
| Wheel Diameter                  | 180 mm (7")  | 230 mm (9")  |
| No Load Speed (RPM)             | 8,500  | 6,600  |
| Sound Pressure Level            | 92 dB(A)   | 91 dB(A)   |
| Sound Power Level               | 103 dB(A)  | 102 dB(A)  |
| Vibration Level                 | Surface Grinding with anti vibration side grip 6.0 m/s²                        | Surface Grinding with anti vibration side grip 4.8 m/s |
| Dimensions (L x W x H)          | 506 x 200 x 146 mm   | 506 x 250 x 146 mm                                     |
| Net weight                      | 6.6 kg *   | 8.5 kg *   |
| Power supply cord               | 2.5 m  | 2.5 m  |
| Standard Equipment: Wh          | eel Cover, Anti-Vibration Grip, Lock Nut Wrench.                               |  |
| Double Insulation               | oust Collection Soft Start Brake Torque Limiter                                | ে Constant Speed (for high voltage areas only)         |
| * Net Weight is including Wheel | Cover Assembly, Vibration proof Grip, Inner Flange and Tool-less Lock Nut Asse | embly  |





