



HG5030

Heat Gun

DELIVERS AIRFLOW UP TO **500 L/min** at **500°C**

1,600W



For Various Applications





Stands upright



1
TEMPERATURE SETTING
Slide Switch

2
STAGE
2 stages

3
AIR TEMPERATURE : °C
350 / 500

4
AIR FLOW : (L/min)
300 / 500

Easy-to-operate slide switch



WIDE VARIETY OF OPTIONAL ACCESSORIES

Glass protection nozzle



Part No.
PR00000028



Wide-slot nozzle



Part No.
PR00000029



Reflector nozzle



Part No.
PR00000030



Reduction nozzle 20



Part No.
PR00000031



Overlap welding nozzle



Part No.
PR00000032



Solder sleeves reflector



Part No.
PR00000033



Welding nozzle



Part No.
PR00000034



Speed welding nozzle



Part No.
PR00000039



SPECIFICATIONS

Continuous rating input	1,600W
Air Temperature (°C) / Flow (L/min)	Slide Switch 1: 350 / 300 Slide Switch 2: 500 / 500
Dimensions (L x W x H)	233x80x208 mm
Net weight	0.56 kg
Power supply cord	2.0 m

 Double Insulation



MAKITA GULF FZE

www.makita.ae |    

MAKITA TOOLS EDITION # 622