

HEAT GUN SERIES

HG6531CK HG6530V HG6030K



MAIN FEATURES

Preset function (HG6531C only)



MODEL	HG6531CK	HG6530V	HG6030K
Temperature setting	Push button switch	Push button switch	Slide switch
Temperature adjustment	by every 5 °C	by every 10 °C	2 stages + cooling mode
Temperature: °C	50 - 650	50 - 650	50 / 300 / 600
Air flow setting	Push button switch	Slide switch	Slide switch
Air flow adjuetment	5 stages	3 stages	3 stages
Air flow: (L/min)	200 - 550	500* / 280 / 550	250* / 250 / 500



Stands upright

* cooling mode

HEAT GUNS	HG6531CK / HG6530V / HG6030K				
		HG6531CK	HG6530V	HG6030K	
Double Insulation	Continuous rating input	2,000W	2,000W	1,800W	
	Air Temperature (°C)	50 - 650	50 - 650	Stage1: 50 / Stage2: 300 / Stage3: 600	
Variable Speed HG6531CK & HG6530V	Air Flow (L/min)	200 - 550 L/min	Stage1: 500 / Stage2: 280 / Stage3: 550 L/min	Stage1: 250 / Stage2: 250 / Stage3: 500 L/min	
	Dimensions (L x W x H)	257x85x206 mm	257x85x206 mm	233x80x208 mm	
Electronic 3-Speed HG6531CK & HG6530V	Net weight	0.71 kg	0.72 kg	0.57 kg	
	Power supply cord	2.0 m	2.0 m	2.0 m	
Carrying Case					
HG6531CK & HG6030K	Standard Equipment: HG6531CK: Includes various types on nozzles. Comes with carry case				
	HG6530V: Noczzles anmd carry case does not come with the tool.				
	HG6030K: Carry Case.				



