



HR006G

XGT Cordless Rotary Hammer (52mm) (SDS-MAX)
Powered by 80V MAX Lithium-Ion Battery

High Performance

With the twin battery system, the tool achieves the 80v max power. Combination of XGT system with powerful brushless motor provides high impact energy of **21.4J** and delivers higher drilling efficiency.

XGT 80Vmax
40Vmax + 40Vmax

21.4J
Impact Energy
(EPTA VALUE)

Good control

With Active Feedback-Sensing Technology (AFT) which turns the motor off, if bit rotation is suddenly forced to stop



2
mode

Rotation +
Hammering
↕
Hammering



Powerful Cordless Rotary Hammer delivers the power, speed, and run-time for corded demands, without the cord

Work amount (drilling) **44 pcs**

With battery: BL4040 x2
Concrete with compressive strength of 40N/mm²
Drilling holes to a depth of 140mm / Ø18mm

BL MOTOR **XPT** **AVT** ANTI VIBRATION TECHNOLOGY **SOFT** NO LOAD **AFT** **AWS**

Low Vibration with Anti-Vibration Technology

More than just a padded handle, AVT is an internal counterbalance that uses air pressure to move counterweight pistons in the opposite direction of the drive piston to actively reduce vibration. In addition, the vibration-absorbing back handle and side handle are engineered to further reduce vibration.

AVT

Counterweight pistons
 Damper spring absorbs impact vibrations from the drill bit
 Vibration absorbing housing isolates handle and motor

"Soft no-load" function
 automatically reduces the speed of the motor when idling to help increase tool life and performance

SOFT NO LOAD

AWS

Auto Wireless Start Function

Bluetooth®

Connects to compatible dust extractor via bluetooth. Dust extractor starts automatically when the tool starts. Also dust extractor stops on its own when the tool is in rest.

Bluetooth Chip (Optional)
 Part #: 198900-7



Extreme Protection Technology

engineered to channel away dust and water for increased durability

XPT

- Variable Speed
- Brake
- Reversing
- Constant Speed
- SDS-MAX Shank
- Torque Limiter
- Built-in Job Light
- Soft Start

Specification

Impact Energy	21.4 J (EPTA Value)
Capacity (with TCT Bit):	52 mm / (with Core Bit): 160 mm
Blows Per Minute (BPM)	1,100 - 2,250
No Load Speed (RPM)	150 - 310
Sound Pressure Level	99 dB(A)
Sound Power Level	110 dB(A)
Vibration Level Chiselling Function :	7.0 m/s ²
Hammer Drilling:	8.5 m/s ²
Dimensions (L x W x H)	610 x 140 x 337 mm (with 4.0Ah battery)
Net weight	11.7 kg (without battery)

Available Variants

VARIANTS	MODELS	BATTERY	CHARGER	WIRELESS UNIT	MAKPAC STACKING CASE
BARE TOOL	HR006G Z	-	-	-	-

Accessories

Dust Extractor Attachment Set (optional accessories)

Engineered to reduce the dust created from concrete drilling / demolition

Set 1: For Drilling and Chiselling / Demolition



For Drilling (concrete)



For Chiselling / Demolition



Set 2: For Chiselling / Demolition



Makita

MAKITA GULF FZE

www.makita.ae

