



HR2663

Combination Hammer with Self Dust Collection System



On-Board Dust Collection System

DX15 [Part No. 191X39-9]
with filter cleaning mechanism

HEPA
filter



Adapted for SDS-PLUS bits

AVT **HEPA**
filter

HEPA filter

Filter cleaning mechanism
by turning the dial, the dust falls off from the filter



Filter plate

Filter plate is engineered to prevent debris entering into motor when using without dust collection system



Enables to accept longer drill bits

Adjustable drilling depth

Telescopic guide also functions as a depth gauge. A desired drilling depth can be adjusted simply by sliding a push button on the guide to the desired point.



Position adjustment of Dust Extraction Inlet

one action adjustment according to bit length simply by pushing a single push button



Secure connection between dust case and dust collecting section allows for less dust leakage

Easy disposal of dust and easy cleaning of dust case

- Dust case cover is easy to open/close with a single operation of a locking tab
- Wide opening of dust case

Dust case
Part No. 199586-0



Transparent dust case for easy checking of collected dust amount



High Dust Collection performance for overhead application

Dust collection rate for overhead application

High

46 holes

Keeps high efficient dust collection

Diameter of drill bit: 10.5mm, Drilling depth: 60mm,
Test Material: Concrete with compressive strength of 40N/mm²

Low

Number of drilled holes

Large Fan Provides Incredibly High Dust Extraction Power



65
mm



High Rotation
Speed

20,900
min⁻¹

Extremely low vibration achieved by ...



1 Damper Spring
absorbs reaction force of impact energy

2 Counterweight mechanism
reduces vibration by moving a counterweight in the opposite direction of the piston

ACCESSORIES

DX15 - On-Board Dust Collection System (Standard Equipment)
Part No. 122B81-7

Dust Case
Part No. 199586-0

Dust Cup Set (Optional Accessory)
Cuff Size - Cuff 22
Part No. 195173-3

Drill Chuck Assembly (Optional Accessory)
Part No. 122574-2

SPECIFICATIONS

Continuous rating input	800W
Impact Energy	2.1 J
Capacity	Concrete : 26 mm; Steel : 13 mm; Wood : 32 mm
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Vibration Level	Hammer Drilling into Concrete : 9.5 m/s ² / Drilling Into Metal : 2.5 m/s ² or less
Dimensions (L x W x H)	666x89x260 mm
Net weight	4.6 kg
Power supply cord	2.5 m

Standard Equipment: Spanner 10 (x 2), Wheel Points.
 Double Insulation



Makita
MAKITA GULF FZE
www.makita.ae |