

HS009G Cordless Circular Saw (235 mm) Powered by 40 V MAX XGT Li-ion BAttery

High Power and Light Weight

The large size Brushless motor combined with XGT system deliver higher power equivalent or higher than corded circular saws

120 cuts (with 5.0Ah battery) (80x300mm Oak wood cutting at 0 degrees 85 mm max cutting depth enables single-pass cutting of a 3x lumber



LIGHT WEIGHT and POWERFUL

Lightweight design and well balanced circular saws for easy maneuverability

Rotatable

Dust Nozzle

Auto-start Wireless System

The wireless activation function enables clean and comfortable operation. By connecting a supported tool to the cleaner, you can run the cleaner automatically along with the switch operation of the tool



Note: Wireless unit is required to activate the Bluetooth Part # : 198900-7 (Optional).

Sub base -

Sub Base can be used as Guide Rule by turning up side down

Twin LED Job Light



Magnesium diecast base Tool weight has been reduced without loss of durability and power. Base fit the with the guide rail directly without any adapter.

| SPECIFICATIONS | | | | | |
|---|---|--|--|--|--|
| Wheel Diameter | 235 mm | | | | |
| Max Cutting Capacity | 0°: 85 mm; 45°: 61 mm; 60°: 44 mm | | | | |
| No Load Speed (RPM) | 4,000 | | | | |
| Vibration Level | Cutting Wood: 2.5 m/s ² or less; Cutting | | | | |
| Sound Pressure Level | 94dB(A) | | | | |
| Sound Power Level | 105 dB(A) | | | | |
| Dimensions (L x W x H) | 413 x 196 x 316 mm | | | | |
| Net weight | 5.7 kg | | | | |
| Standard Equipment: Sub Base, Hex Wrench. | | | | | |

OTHER OPTIONAL ACCESSORIES



Guide rail holder 1.4M - B-57613 14M - E-05664



Type A. 194385-5 Type B. 199826-6

Clamp set









with positive stops at 22.5° and 45°



Heavy duty power with constant speed control maintaining blade speed under load

Electric brake system

enables you to start the next operation quickly

Soft start

feature for smooth start-ups

Anti-Restart

feature prevents accidential startup

Extreme Protection Technology

Integrated seals designed to improve a tool's operation in harsh conditions by channeling water and dust from key internal components.

| Variants | Battery | Charger | Carry Case |
|-----------|---|------------------|-----------------------|
| HS009G T2 | YES, 2pcs of 40V MAX XGT 5.0Ah battery | YES, 1pc Charger | Plastic Carry Case |
| HS009G Z | NO | NO | NO |

EFFICUT TCT SAW BLADE (FOR WOOD)

| <i>SEFFICUT</i> | | | | | | | | |
|---------------------------|-------|-------|-------|-------------|-------|----------|--|--|
| Dia | Bore | Kerf | Plate | Rake | Teeth | Part No. | | |
| 235mm | 20mm | 2.2mm | 1.5mm | 20 ° | 24T | E-01959 | | |
| 235mm | 30mm* | 2.2mm | 1.5mm | 20 ° | 24T | E-01909 | | |
| To be used with 25mm ying | | | | | | | | |

be used with 25mm rin



Guide rail joint 198885-7

Splinter guide for Guide rail

