



HS011G

Cordless Circular Saw (260/270 mm)

Powered by 40 V MAX XGT Li-ion BATTERY

High Power and Light Weight

The large size Brushless motor combined with XGT system deliver higher power equivalent or higher than corded circular saws

40 cuts (with 5.0Ah battery)

(90x1000mm Melapicutting at 0 degrees)

The test results depends on the hardness of the test material, etc.)

101 mm max cutting depth
enables single-pass cutting of a 4x lumber



LIGHT WEIGHT and POWERFUL

Lightweight design and well balanced circular saws for easy maneuverability

Auto-start Wireless System

The wireless activation function enables clean and comfortable operation. By connecting a supported tool to the cleaner, you can run the cleaner automatically along with the switch operation of the tool




Note: Wireless unit is required to activate the Bluetooth Part #: 198900-7 (Optional).

Rotatable Dust Nozzle

Bevel cuts up to 1° left and 60° right

with positive stops at 22.5° and 45°



Heavy duty power with **constant speed control** maintaining blade speed under load

Electric brake system enables you to start the next operation quickly

Soft start feature for smooth start-ups

Anti-Restart feature prevents accidental startup

Sub base

Sub Base can be used as Guide Rule by turning up side down



Twin LED Job Light



Magnesium diecast base


Tool weight has been reduced without loss of durability and power. **Base fit the with the guide rail directly without any adapter.**

Extreme Protection Technology

Integrated seals designed to improve a tool's operation in harsh conditions by channeling water and dust from key internal components.

SPECIFICATIONS	
Wheel Diameter	260 - 270 mm
Max Cutting Capacity	0°: 97 - 101 mm; 45°: 68 - 71 mm; 60°: 48 - 51 mm
No Load Speed (RPM)	3,500
Vibration Level	2.5 m/s or less
Sound Pressure Level	93dB(A)
Sound Power Level	104 dB(A)
Dimensions (L x W x H)	453 x 196 x 336 mm
Net weight	6.7 kg
Standard Equipment: Sub Base, Hex Wrench.	

Variants	Battery	Charger	Carry Case
HS011G T2	YES, 2pcs of 40V MAX XGT 5.0Ah battery	YES, 1pc Charger	MAKPAC
HS009G Z	NO	NO	NO

TCT SAW BLADE 						
Dia	Bore	Kerf	Plate	Rake	Teeth	Part No.
260mm	25mm	2.15mm	1.5mm	23°	24T	E-07733*
270mm	25.4mm	2.15mm	1.5mm	20°	24T	E-12974

* Standard Equipment

OTHER OPTIONAL ACCESSORIES						
Guide rail 1.4M - 194368-5 3M - 194367-7 	Guide rail holder 1.4M - B-57613 1.4M - E-05664 	Guide rail joint connector 2pcs set 198885-7 	Splinter guide for Guide rail 423360-7 	Clamp set (use with Guide rail) Type A. 194385-5 Type B. 199826-6 	Bevel guide 196664-7 	



MAKITA GULF FZE

www.makita.ae |    

MAKITA TOOLS EDITION # 586