

JR001G

XGT - Cordless Reciprocating saw

XGT
40V Li-ion
max **BL** **XPT**
MOTOR

Effective Lubricating mechanism of slide switch



Rigid Shoe

- Shoe has been reinforced.
- Fixed type shoe is used for added durability


Rubber Joint Structure

The tool body is separated into the upper and lower housings which joined with vibration absorbing cushion rubbers to reduce load on battery and terminal

High Power and lightweight

Higher power delivered by the BL motor designed to best suit XGT battery. Lightweight achieved by employing one XGT battery drive but with High power

Smooth cutting with vertical crank system



The crank mechanism has been designed to rotate vertically to provides less vibration to the user

Tool-less shoe adjustment



Lever system has been designed for easier adjustment

Easy blade ejection lever



Simply insert the blade for installation. Removal can be done with single action no need to touch the blade. A great feature when working with hot blades.

Lightweight, Powerful, Durable and Built to perform

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Possibility to choose two different speed settings, stroke length of 32 mm and stroke rate of 0-3 000 min⁻¹ with continuous control from the switch. Saw is also equipped with quick-release blade attachment for fast and effortless blade change.



Specification

Length of Stroke	32 mm
Strokes Per Minute (SPM)	High / Low: 0 - 3,000 / 0 - 2,300
Capacity	Pipe : 130 mm / Wood: 255 mm
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Dimensions (L x W x H)	472x88x239 mm
Net weight	4.5kg

Available Variants

TYPE	VARIANTS	BATTERIES	CHARGER	CARRY CASE
W/O Battery / Charger	JR001G Z	-	-	-
With Battery / Charger	JR001G M2	BL4040 (4.0Ah) 2pcs	DC40RA 1pc	Plastic Case



MAKITA GULF FZE

www.makita.ae |    