



KT001G
CORDLESS KETTLE
Powered by 40V MAX XGT Li-ion battery



Water Tank Capacity 0.8 L	Boiling Time (From starting temperature of 23°C (approx.)) 8 min	Battery BL4040 x2 capacity of boiling water (23°C) (approx.) 2.2 L
--	--	---

Powered by 40Vmax XGT Li-ion battery



Battery box is able to hold two XGT batteries in parallel



HOT WATER, ANYTIME... ANYWHERE...



Dual layer structure

Stainless steel interior plus plastic exterior * provides high heat retention while keeping Kettle surface cool



* There is a insulating layer of air between the interior and exterior layers

Easy to carry around

Kettle can be transferred easily on Power supply stand by holding the carrying handle of the stand



Power switch



Anti-spill lock button

Provided to minimize spilling of hot water even if Kettle falls over



Removable lid

Removable for easy water supply and cleaning

Removable filter for filtering dust, lime scale and more



Auto shut-off after boiling

Boil-dry Protection

Easy to read water scale



Kettle can be turned on only when grounded



Ground Sensor

Powered by 40Vmax XGT Li-Ion battery



Battery box is able to hold two XGT series batteries

Water Tank Capacity

0.8 L

Boiling Time

(From starting temperature of 23°C) (approx.)

8 min

Battery BL4040 x2 capacity of boiling water (23°C) (approx.)

2.2 L

SPECIFICATIONS

Boiling Time (From starting temperature of 23°C) (approx.)	8min (0.8L water)
Water tank capacity	0.8 L
Dimensions (L x W x H)	Kettle on Power supply stand: 233 x 263 x 307 mm
Net weight	1.0kg (without battery)

Approx amount of hot water for making drinks/foods

Instant/drip coffee	0.2 L
Instant cup noodles	0.15 - 0.23L
Instant cup soup	0.3 - 0.5L

Boiling time (approx.) of 0.8L water

Starting water temperature	10°C	23°C	40°C
	9 min	8 min	6 min

Variants	Battery	Charger	Carry Case
KT001GZ	NO	NO	NO



MAKITA GULF FZE

www.makita.ae

