



ML005G

Cordless Work Light

Powered by 40V MAX XGT Li-ion battery / 18V LXT Li-ion battery

MAX. LUMINOUS FLUX

3,600 Lm



Continuous run time (approx)
on a full battery charge

High / Medium / Low

3.5 / 7.5 / 15 h

Battery: BL4040

Powered By:

- 40Vmax XGT Li-ion battery
- 18V LXT Li-ion battery



Max Luminous Flux


3,600 lm




3 Brightness settings

with memory function that remembers the brightness setting last 3,600 lm time you power off

Switch




High
3,600 lm



Medium
1,800 lm



Low
900 lm




Front: About **6** m
Side: About **6.4** m



Distance

Battery Capacity Warning Function



Automatically notifies the user about a decrease in battery capacity with a reduction in illuminance

Carrying Handle



Compact design with a short height thanks to the retractable carrying handle

Angle Adjustment



Knob for free adjustment of light angle enables the light source to rotate from -30° to 210° to a desired angle

Dust and Water resistance (only with DC power)

IP65

For use in outdoor applications or harsh environments

ACCESSORIES

LAMP SHADE

Part No. **GM00002358**


- Provides widespread illumination and reduces the glare of LED light
- Reduces multiple shadows



ANTI-GLARE FILM

Part No. **GM00002359**

reduces glare



WISE

Part No. **GM00001396**



FLAT BAR

Part No. **GM00002379**



TRIPOD

Part No. **GM00002378**



SPECIFICATIONS

Illuminance (High / Mid / Low)	at 1m from the light source: 2,100 / 1,000 / 500 lx
Luminous Flux	High / Mid / Low: 3,600 / 1,800 / 900 lm
Continuous illumination	High / Mid / Low: 3.5 / 7.5 / 15 h
Dimensions (L x W x H)	w/ Handle in Retracted Position: 248 x 309 x 296 mm w/ Handle in Upright Position: 248 x 309 x 423 mm
Net weight	4.6 kg

VARIANTS

ML005GX
(Comes with Lamp Shade)

BATTERY

NO

CHARGER

NO

CARRY CASE

NO



MAKITA GULF FZE

www.makita.ae |    