



**ML006G** XGT **40V** Li-Ion max  
CORDLESS FLASHLIGHT

**DML816** 18V LITHIUM-ION

# ROTATABLE AND FOLDABLE

Continuous Runtime  
on a full battery charge

**ML006G**

**82h**

Battery: BL4040  
Low Mode

**DML816**

**75h**

Battery: BL1860B  
Low Mode

Max. luminous flux

**500 lm**

**ML006G**



**DML816**





### Rotatable and foldable light head



Foldable light head

Rotatable light head



Can be used as a compact stationary lamp with the light head swivelled and folded fully

ML006G



DML816



#### Light diffusing lens

- softens the light of LED to reduce glare
- provides widespread illumination



#### Large hook

- Light head is rotatable with the flashlight hanging down




- Retractable back into the upper portion of handle

#### Battery capacity warning

This system warns user by reducing the number of ON LED lights down to 1 before the battery is empty.

#### 3-stage brightness adjustment

High → Medium → Low → OFF




### ACCESSORIES

#### Lamp shade

Part No. GM00001326

By attaching to the Cordless Flashlight ML006G / DML816, the irradiation range is widened and the glare of the light source is reduced



#### Shoulder Hook Set

Part No. GM00001288



### SPECIFICATIONS

	ML006G	DML816
Run Time (hrs)	Up to: 82 (Low mode, with BL4040)	Up to: 75 (Low mode, with BL1860B)
Illuminance (at 0.5m from the light source)	High/ Medium/ Low: 800 / 400 /180 lx	High/ Medium/ Low: 800 / 400 /180 lx
Luminous Flux	High/ Medium/ Low: 500 / 250 / 100 lm	High/ Medium/ Low: 500 / 250 / 100 lm
Dimensions (L x W x H)	275 - 408 x 85 x 148 mm (with BL4040)	267 - 400 x 79 x 127 mm with BL1860B)
Net weight	0.4 kg (w/o battery)	0.42 kg (w/o battery)

**Standard Equipment:** Shoulder Hook Set, Lamp Shade.



Variants	Battery	Charger	Carry Case
ML006G	NO	NO	NO
DML816	NO	NO	NO



MAKITA GULF FZE

www.makita.ae |