

## **ML009G**

## **Cordless Work Light**

Powered by 40V MAX XGT Li-ion battery / 18V LXT Li-Ion battery















# 3 Brightness settings

with memory function that remembers the brightness setting last 3,600 Im time you power off



High 10,000 lm



Medium 4,000 lm



Low 2,000 lm




**LED Light Color: Daylight White** 



DUST AND WATER RESISTANCE

**Color Temperature:** 5,000 K



**Carrying Handle** 



Compact design with a short height thanks to the retractable carrying handle



light source to rotate from battery capacity with a

**Battery Capacity** Angle Adjustment Warning Function

**Switch** 



Knob for free adjustment Automatically notifies the of light angle enables the user about a decrease in -30 ° to 210 ° to a desired reduction in illuminance

### **ACCESSORIES**

**Distance** 

### **LAMP SHADE** Part No. GM00002377

· Provides widespread illumination and reduces the glare of LED light

· Reduces multiple shadows



### **ANTI-GLARE FILM** Part No. GM00002376

When the light source is glaring, attach this film to the lens surface of the light to reduce the glare



### **VISE** Part No. GM00001396







5 / 2.4 (with BL4040 x 2) source: 4,300 / 1,900 / 1,000 lx 000 / 4,000 / 2,000 lm
000 / 4,000 / 2,000 lm
. , . ,
4 m
ed Position: 248 x 386 x 305 mm
t Position: 248 x 386 x 430 mm
ry)
_

VARIANTS	BATTERY	CHARGER	CARRY CASE
ML009G	NO	NO	МО



