



ML010G

Cordless Upright Area Work Light

Powered by 40V MAX XGT / 18V LXT / 14.4V LXT / AC

Improved Self-righting Performance



Up to 4 batteries can be installed in parallel
two LXT batteries +
two XGT batteries



Continuous Run time (approx)

two LXT batteries +
two XGT batteries

Low Mode **59** hours

Battery: BL4080F x 2 & BL1860B x 2
All LEDs light up

Maximum Luminous Flux

5,500 lm



A VERSATILE AND CONVENIENT
LIGHTING SOLUTION
THAT DELIVERS BRIGHT ILLUMINATION
IN ANY WORK ENVIRONMENT



Compatible with 3 Power Sources



two in parallel or one



two in parallel or one



Inlet type AC power supply cord

3 Brightness Settings

with memory function of the setting last time you power off



LOW
1,500 lm



MEDIUM
3,000 lm



HIGH
5,500 lm

Lighting Area Selection



LEFT
180°



360°



RIGHT
180°

Battery Capacity Warning Function



Light automatically dims and a single LED remains illuminated once battery charge starts running low, automatically notifying the user

Battery Fuel Gauge

Color LED to indicate the each battery usage status

Padlock Hole

anti-battery theft



Rounded base design

a self-righting rounded base design prevents the lighting from being knocked over

AC outlet - Up to 8 units can be connected together from the AC outlet. Also equipped with a circuit breaker for protection from overload



Diffusing Lens

Daylight white (approx 5,500K)

Carrying Handle



Allows for easy handling and relocation of the light, increasing convenience for the user

Reflector

glows in the dark to help you locate the worklight body

IP54 standard protection

(Only with DC power supply)
Safeguarding against dust, moisture and water sprays from all directions, making it suitable for various environments



Continuous run time (approx) - All LEDs lit up

Battery	High	Medium	Low
BL1860B x2	4.5h	8.5h	16h
BL4040 x2	6.5h	11h	21h
BL4050F x2	8.5h	14h	27h
BL4040 x2 + BL1860B x2	11h	19.5h	37h
BL4050F x2 + BL1860B x2	13h	22.5h	43h
BL4080F x2	13h	23h	43h
BL4080F x2	17.5h	-	59h

SPECIFICATIONS - ML010G 40VMAX / 18V / 14.4V / AC

Illuminance (High / Med. / Low)	550 / 300 / 150 lx (at 1 m from the light source)
Luminous flux	5,500 / 3,000 / 1,500 lm (High / Med. / Low)
Continuous run time on full battery charge	4.5 / 8.5 / 16 hours (High / Med. / Low) (with BL1860B x 2)
	6.5 / 11 / 21 hours (High / Med. / Low) (with BL4040 x 2)
	8.5 / 14 / 27 hours (High / Med. / Low) (with BL4050F x 2)
	11 / 19.5 / 37 hours (High / Med. / Low) (with BL4040 x 2 & BL1860B x 2)
	13 / 22.5 / 43 hours (High / Med. / Low) (with BL4050F x 2 & BL1860B x 2)
	13 / 23 / 43 hours (High / Med. / Low) (with BL4080F x 2)
Dimensions (L x W x H)	490 x 490 x 814 mm
Net weight	14.04 kg (without battery)
Power supply cord	2.5 m

Standard Equipment: AC Power Cord, Earth Grounding Plug.

VARIANTS	Battery	Charger	Carry Case
ML010G Z	NO	NO	NO



MAKITA GULF FZE

www.makita.ae |