

ML011G

Cordless Work Light
Powered by 40V MAX XGT Li-ion battery

THREE LIGHTING MODES

With 2 LEDs for sidelighting & uplighting





Max. Luminous Flux 300 Im

Three Lighting Modes

Equipped with 2 LEDs - One for sidelighting and the other for uplighting, for wide-angle illumination.

Mode Memory Function:

The appliance saves the lighting mode at the time when turned off by press and holding the light switch button.

(This mode is remembered even if the battery is removed after that)











USB On/Off switch LED Switch Button



USB output port

- 1 Port (Type A for DC5V/2.4A)
- With Auto-OFF function (after 30 mins of no operation)
- With Output Indication Lamp



USB

Compact Design

Minimal size of the appliance has been achieved for space saving use and storage by designing it on the basis of the size of compatible battery



Can be used for downlighting

With optional "Strap with hook" fastened to the two Strap holes on the appliance, the light can be used for downlighting by hanging it upside down



Strap with hook (optional accessory)

SPECIFICATIONS				
Illuminance (at 0.5 m from	Sidelighting + Uplighting /			
the light source)	Sidelighting only / Uplighting only: 240 / 190 / 190 lx			
Luminous flux	Sidelighting + Uplighting /			
	Sidelighting only / Uplighting only: 300 / 150 / 150			
Run time (hrs)	37 (with BL4040 at 300 lm)			
	64 (with BL4040 at 150 lm)			
Dimensions (L x W x H)	107 x 77 x 50 mm (without battery)			
Net weight	0.19 kg (without battery)			

	Variants	Battery	Charger	Carry Case
	ML011G Z	NO	NO	NO

ACCESSORIES

Strap with Hook Part No. SE00001178

Strap with hook is fastened to the two Strap holes on the appliance, the light can be used for downlighting by hanging it upside down











