

PM001G Cordless Cordless Backpack Mist Blower Powered by 40V MAX XGT Li-ion battery

POWERFUL CORDLESS MIST BLOWER

POWER AND VERSATALITY SIMILAR TO PETROL ENGINE MIST BLOWERS





Solution Tank Capacity

15L

Max. Spraying Range High spraying speed mode

14 m

(horizontal)

Continuous Run Time on a full battery charge High spraying speed mode



Average Particle Size High spraying speed mode







The opening / closing operation of the solution supply valve is interlocked with switch trigger to suppress dripping of solution

Max Spray Distance: 14m





3 spraying speed modes



Selectable with the button on control handle
With mode memory function
(In the next operation, the machine will

	time user turned off		
	resume operation in the same mode as last		
(in the next operation, the machine will			

High spraying speed mode	Long distance spraying allows for outdoor operation
Medium spraying speed/Low spraying speed mode	For indoor operation or runtime-oriented operation

ULV compatibility

 Compatible with ULV (Ultra Low Volume) spray for pesticides, etc. Only available in High spraying speed mode

Nozzle type	Average particle size
ULV nozzle	50µm
Standard nozzle	150µm

Powered by 40Vmax XGT **Li-lon battery** (two in parallel or one)



Automatic battery switching

If two batteries are installed and one battery in use has run out of power, the battery system automatically switches to use to the other one

Continuous Run Time on a full battery charge High spraying speed mode



A variety of front covers **Diffusion Cover** You can diffuse the mist by attaching the diffusion cover to the end nozzle Deflector Set

(optional) You can discharge the mist upward or downward by attaching the deflector to the end nozzle







Variable Grip



Tank filter port diameter 0.5mm (max)

SPECIFICATIONS

Chemical tank capacity	15.0 L (507 oz)
Max air volume	High / Med. / Low: 14.3 / 11.0 / 9.0 m³/min
Max air velocity	High / Med. / Low: 64.0 / 52.0 / 42.0 m/s
Avg. air velocity	High / Med. / Low: 53.0 / 43.0 / 34.0 m/s
Vibration level	2.5 or less
Sound pressure level	84.5 dB (A)
Sound power level	103.3 dB (A)
Continuous Use (min.)	w/ BL4080F x2 High: 20
Dimensions (L x W x H)	320 x 600 x 690 mm (without Nozzle)
Net weight	11.9 kg (without Battery)
Variable Speed	nstant Speed 74 Electronic 4-Speed

Variants	Battery	Charger	Carry Case			
PM001G L202	2pcs 40V MAX XGT 8.0Ah batteries	lpc 2 Port Charger	NO			
PM001G Z01	NO	NO	NO			
ACCESSORIES						

Diffusion Cover Deflector Cover Part No. 453506-1 Part No. 198248-7



Part No. 196733-4



