



PV301D **CXT**

CORDLESS SANDER POLISHER



BL
MOTOR **XPT**

COMPACT AND HIGHLY EFFICIENT
HIGH MANEUVERABILITY AND LONG RUN TIME

Compact
head length

127 mm

Light Weight

1.2 kg
(with BL1041B)

Long continuous
operation time

Polishing performance
comparison*

* tested with normal load of 1.6kg,
on a full battery charge

18 min
(with BL041B)



SHORTENED HEAD LENGTH for increased maneuverability



High/Low 2-speed selection with variable speed in each range enables to adjust the speed setting to match user's needs.

- 1: Low (for polishing) 0 - 2,800 min⁻¹
- 2: High (for sanding) 0 - 9,500 min⁻¹



ACCESSORIES

For polishing work

Pad 75

Diameter: 75mm
Easy to change Hook & Loop style
Part No. 191N91-7

Sponge pad and Wool pad



Sponge pad (standard equipment)

Diameter: 80mm

For applying wax, removing wax and polishing

Shape	Part No.	Shape	Part No.
	191N90-9		191N91-7

Wool pad 80mm


Diameter: 80mm
For surface treatment
(standard equipment)

Shape	Part No.
	191N92-5

For sanding work

Pad 50

Diameter: 46mm
Twist-on/twist-off style applicable to heavy-duty operation
Part No. 743124-6



Adapter
Part No. 743126-2
(standard equipment)

Surface conditioning disc

Diameter: 50mm, Twist-on/twist-off type, 25pcs/set
For Material: Metal / Stainless, Aluminium

Type	Application	Part No.
	• Surface polishing	Coarse E-07462
	• Removing paint/rust	Medium E-07478
		Fine E-07484
	• Surface polishing	Medium E-07490
		Fine E-07509
		Very fine E-07515

Fiber sanding disc

Diameter: 50mm, Twist-on/twist-off type, 25pcs/set
For Material: Metal / Stainless, Aluminium

Grit	Application	Part No.
A60	• Grinding	E-07412
A80	• Chamfer	E-07428
	• Deburring	
A120	• Surface polishing	E-07434
Z60	• Grinding	E-07440
	• Chamfer	
Z80	• Deburring	E-07456

Toolless pad replacement



BL
MOTOR

Brushless motor

XPT
eXtreme Protection
Technology



Dust cover

Lock-on switch

12Vmax
LITHIUM-ION



Fiber sanding disc and Surface conditioning disc

Pad 50

Adapter

SPECIFICATIONS

Pad / Disc Diameter	Twist-On / Twist-Off Style: 50 mm Hook & Loop Style: 80 mm
Backing Pad Diameter	Twist-On / Twist-Off Style: 75 mm Hook & Loop Style: 46 mm
No Load Speed (RPM)	Polishing: 0 - 2,800, Sanding: 0 - 9,500
Continuous Use (min.)	w/ BL1041B: 18
Head Length	127 mm (5")
Dimensions (L x W x H)	w/o Battery: 133 x 67 x 201 mm w/ BL1041B: 139 x 67 x 249 mm
Net weight	1.2 kg

Standard Equipment: Side Grip, Pad, Adapter, Wool Pad, Sponge Pad.

Variable Speed Mechanical 2-Speed Constant Speed

Variants	Battery	Charger	MAKPAC Carry Case
PV301DZ	NO	NO	NO



Makita

MAKITA GULF FZE

www.makita.ae |