



TW005G

XGT Cordless Impact Wrench (1/2")
Powered by 40V MAX Lithium-Ion Battery

HIGH POWER | HIGH PERFORMANCE | HIGH DURABLE

High power brushless motor provides

Nut-busting torque

630
Nm

Max fastening torque

350
Nm

High power 40Vmax XGT Li-Ion battery reduces the current load on the controller, allowing for continuous operation

Number of bolts consecutively tightened under heavy load

approx
560 bolts

(with 5.0Ah battery)
(Tightening of M16 bolts)

XGT
40V Li-ion
max

BL
MOTOR **XPT**

Compact design with a short overall length of 144mm Lightweight Design - 1.2kg (without battery)


Electronic 4 stage impact power selection

Both in forward and reverse rotation modes, for a wide range of applications



Full speed mode

- Variable speed mode can be changed to full speed mode by pushing a button.
- Reduces trigger pull to reach full speed, decreasing hand fatigue & increasing efficiency.



Hammer case cover securely fastened with four bolts

Phosphorescent bumper

Pin detent

Twin LED job Light



Reinforced gear housing provides additional durability on the job site



High-strength anvil

Double spring

Constant speed control

reduces the torque drop when remaining battery capacity gets low

For Various applications



Auto-stop system available both in forward / reverse rotation modes

3 forward and 3 reverse rotation auto-stop modes offer increased efficiency when fastener is adequately loosened

	Forward	Reverse
mode 1	The tool stops automatically as soon as it has detected the first impact blow.	The tool stops automatically as soon as it has stopped impact blow.
mode 2	The tool stops automatically approximately 0.5 seconds after the moment it has detected the first impact blow.	The tool stops automatically approximately 0.2 seconds after the moment it has stopped impact blow.
mode 3	The tool stops automatically approximately 1.0 second after the moment it has detected the first impact blow.	The tool automatically slows down to 300min ⁻¹ after the moment it has stopped impact blow.

Specification

Fastening Capacities	Standard Bolt: M10 - M20 (3/8" - 3/4") High Strength Bolt: M10 - M16 (3/8" - 5/8")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	Max / Hard / Mid / Soft: 0 - 3,200 / 2,600 / 1,800 / 1,000
Impacts Per Minute (IPM)	Max / Hard / Mid / Soft: 0 - 4,000 / 3,400 / 2,600 / 1,800
Max Fastening Torque	350 N·m (260 ft.lbs.)
Nut-Busting Torque	630 N·m (465 ft.lbs.)
Vibration Level	16.5 m/s ²
Sound Pressure Level	99 dB(A)
Sound Power Level	110 dB(A)
Dimensions (L x W x H)	w/ BL4040: 144x86x253 mm
Net weight	1.2 kg (without battery)

Available Variants

VARIANTS	MODELS	BATTERY	CHARGER	MAKPAC STACKING CASE
BARE TOOL	TW005G Z	-	-	-
KIT VERSION	TW005G M2	2pcs of BL4040 (4.0Ah)	1pc of fast charger DC40RA	Type 2

Accessories

Tool hanger set (optional)
191F58-7



MAKITA GULF FZE

www.makita.ae |