

HIGH POWER

Driving shank: 12.7mm (1/2") Square

Ultra-compact design at only 150MM long and weighs only 1.2 kg (with 4.0Ah battery) for reduced operator fatigue



When the bolt/nut gets loosened enough, the tool stops in 0.2 seconds

Technical Specifications			
Fastening Capacities	Standard Bolt: M8 - M16 (5/16" - 5/8")		
	High Tensile Bolt: M6 - M12 (1/4" - 1/2")		
Square Drive	12.7 mm (1/2")		
No Load Speed (RPM)	High / Low: 0 - 2,400 / 0 - 1,300		
Impacts Per Minute (IPM)	High / Low: 0 - 3,600 / 0 - 2,000		
Max Fastening Torque	165 N·m		
Dimensions (L x W x H)	w/ BL1021B: 150x66x213 mm		
	w/ BL1041B: 150x66x232 mm		
Net weight	1.1 - 1.2 kg		
Variable Speed	rsing Built-in Job light		

Electronic 2-Speed

Carry Case

AVAILABLE VA	RIANTS			
AMPERE	VARIANTS	BATTERIES	CHARGER	PLASTIC CASE
W/O BATTERY/ CHARGER	TW161D Z	0	-	-
4.0Ah	TW161D SME	2	YES	YES

Standard Equipment: Belt clip.

Marake



makita