LIGHT WEIGHT | COMPACT | HANDY
ENABLES EASY PRUNING AND CUTTING BRANCHES OR SMALL TREES

Automatic
Chain
Lubrication

NET WEIGHT 1.22 kg
Without Battery

12v max
LITHIUM-ION

BL MOTOR XPT

Movable Guard
covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch

Lock-off Lever accessible from both sides

Flexible Rubber Guard for hand

Guide Bar Length
100 mm

Work Amount
Test Conditions:
Cut ø50 cedar wood under an optimal pressing load of 20N or less on cutting edge. Saw chain: 80TXL

73 pcs
Saw chain: 80TXL

Battery: BL1021B

## Automatic Chain Lubrication

Oil Tank Cap | Chain Oil View Window

New Tool-less change and tension adjustment of saw chain

- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain
- This easy-to-operate large lever is designed to be pulled up and turned easily

BL MOTOR
Compact and Lightweight BL Motor

XPT
eXtreme Protection Technology

ACCESSORIES

Guide Bar 4 Set
Part No. 1910W0-3
Bar Length: 10cm/4"
No. of drive links: 26
Gauge: 1.1mm/0.043"
Type: 80TXL
Cutter Type: MC

Saw Chain 4 Set
Part No. 1910V6-4
No. of drive links: 26
Gauge: 1.1mm/0.043"
Pitch: 0.325" LP
Type: 80TXL
Cutter Type: MC

Holster Set
Part No. 1911R0-4

SPECIFICATIONS

Guide Bar Length	100 mm
Saw Chain	Type: 80TXL
	Pitch: 0.325"
	Gauge: 1.1 mm (0.043")
Chain Speed	8.0 m/s (480 m/min) (1,570 FPM)
Chain Oil Tank Volume	55 mL (1.9 USoz)
Vibration Level	Front : 4.8 m/s² / Rear : 4.1 m/s²
Dimensions (L x W x H)	357 x 90 x 215 mm (without Battery)
Net weight	1.22 kg (without Battery)

Standard Equipment: Saw Chain, Guide Bar, Guide Bar Case, Round File

Brake   Constant Speed

Variants	Battery	Charger	Carry Case
UC100D **WA**	1pc 12V MAX CXT Li-ion 2.0Ah battery	1pc Charger	NO
UC100D **Z**	NO	NO	NO

MAKITA GULF FZE
www.makita.ae