

Angle drill LXT DDA450ZK



Product Description

18V LXT • 25 Nm • 0 - 1 400 min⁻¹

LXT® powered angle drill for tight spaces

Compact and lightweight for increased maneuverability in various work postures and reduced user fatigue. High-speed drilling beyond AC powered tool.

Product Specifications

Drilling Capacity Wood (Auger Bit)	38 mm
Vibration Level (3 axes), Drilling	= 2,5 m/s ²
Drilling Capacity Wood (Self-feed bit)	50 / 65 mm
Max. Drilling Diameter in Steel	13 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	3,2 - 3,5 kg
Brushless Motor	YES
Battery Voltage	18 V
Sound Pressure Level	83 dB(A)
Product Dimensions (L x W x H):	434 x 82 x 179 mm
Max. fastening torque Hard/Soft	70 / 26 Nm
Sound Power Level (L<sub>WA</sub>)	94 dB(A)
Voltage LXT	1
Product net weight (new)	2,9 kg
System	LXT 18V/36V
Vibration Uncertainty (K Factor)	1,5 m/s ²
Angle length	179 mm
Driving Shank	1/2" -20UNF
Noise Uncertainty (K Factor)	3 dB(A)
Drill Chuck Capacity	1,5-13 mm
No load speed	0 - 450 / 1400 min ⁻¹

Standard Equipment

⊙ With Carry Case and Sold without Battery or Charger

More info

<https://makita.ae/product/angle-drill-lxt-dda450zk/>