

## Angle Grinder, 115 mm GA4595



### Product Description

1 900 W • 115 mm • 11 500 min<sup>-1</sup>

#### Durable 1900 W angle grinder.

Corded paddle switch type angle grinder with improved power consumption and durability. Equipped with AFT (Active Feedback sensing Technology) for kickback reduction. Also features variable speed control by dial and mechanical brake.

### Product Features

- ⊙ Anti-restart function minimizes accidental start-up
- ⊙ Soft start feature for smooth start-ups

### Barcode

88381771696

### Product Specifications

Power Supply Cord UK	2,5 m
Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	5,4 m/s <sup>2</sup>
Grinding Disc Diameter	115 mm
Max. Depth of Cut	26 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s <sup>2</sup>
Sound Pressure Level	94 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s <sup>2</sup>
Power Supply Cord	4,0 m
Product Dimensions (L x W x H):	326 x 130 x 123 mm
Continuous Input Power	1900 W
Sound Power Level (L <sub>WA</sub> )	102 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	2,6 - 3,8 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2100 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s <sup>2</sup>
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
Dead Man's Switch (No Lock-On)	1
No load speed	11500 min <sup>-1</sup>

### More info

<https://makita.ae/product/angle-grinder-115-mm-ga4595/>