

Angle Grinder 125 mm

GA5091



Product Description

1 900 W • 125 mm • 2 800 - 11 500 min⁻¹

Corded angle grinder with improved power consumption and durability

GA5091 Angle Grinder has SJS II technology, Active Feedback sensing Technology, Anti-Restart Function, Mechanical Brake, Soft Start and Slide Switch.

Product Features

- ⊙ Anti-restart function minimizes accidental start-up
- ⊙ AFT (Active Feedback sensing Technology) turns the motor off if rotation speed suddenly slows or wheel is forced to stop
- ⊙ Super Joint System II developed for effective vibration absorption

Barcode

88381768443

Product Specifications

Power Supply Cord UK	2,5 m
Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	8,7 m/s ²
Max. Depth of Cut	31 mm
Grinding Disc Diameter	125 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	90 dB(A)
Vibration Level, Disc Sanding	3,0 m/s ²
Power Supply Cord	4,0 m
Continuous Input Power	1900 W
Product Dimensions (L x W x H):	349 x 140 x 129 mm
Sound Power Level (L _{WA})	98 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	2,8 - 4,0 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2100 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
No load speed	2800 - 11500 min ⁻¹

More info

<https://makita.ae/product/angle-grinder-125-mm-ga5091/>