

# Angle Grinder

## 9562CR



### Product Description

1 200 W • 125 mm • 12 000 min<sup>-1</sup>

#### Compact tool for cutting and grinding

Angle grinder with 1 200 W motor and 125 mm wheel. Labyrinth channel construction protects the armature and the field coil from impurities in the cooling air. Equipped with a slide switch.

### Product Features

- ⊙ Electronic soft start feature for smooth start ups
- ⊙ Labyrinth construction seals and protects motor and bearings from dust and debris for longer tool life
- ⊙ Ergonomically balanced for easy handling
- ⊙ Ergonomic and easy to use

### Barcode

88381098014

### Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	8,5 m/s <sup>2</sup>
Grinding Disc Diameter	125 mm
Power Supply Cord	2,5 m
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s <sup>2</sup>
Product Dimensions (L x W x H):	289 x 139 x 103 mm
Max Output Power	2000 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s <sup>2</sup>
Anti-Restart Function (NVR Switch)	1
Sound Pressure Level	83 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Weight Without Cable (EPTA)	2,3 kg
Continuous Input Power	1200 W
Tool Category	Grinding, Sanding and Polishing
No load speed	2800 - 12000 min <sup>-1</sup>
Spindle Thread	M14
Sound Power Level (L <sub>WA</sub> )	94 dB(A)

More info

<https://makita.ae/product/angle-grinder-9562cr/>