

# Angle Grinder

## 9562CR



### Product Description

1 200 W • 125 mm • 12 000 min<sup>-1</sup>

#### Compact tool for cutting and grinding

Angle grinder with 1 200 W motor and 125 mm wheel. Labyrinth channel construction protects the armature and the field coil from impurities in the cooling air. Equipped with a slide switch.

### Product Features

- ⊙ Electronic soft start feature for smooth start ups
- ⊙ Labyrinth construction seals and protects motor and bearings from dust and debris for longer tool life
- ⊙ Ergonomically balanced for easy handling
- ⊙ Ergonomic and easy to use

### Barcode

88381098014

### Product Specifications

|   |                                 |
|---|---------------------------------|
| <b>Bore Size (Arbor Diameter)</b>                         | 22,23 mm                        |
| <b>Vibration Level, Surface Grinding</b>                  | 8,5 m/s <sup>2</sup>            |
| <b>Grinding Disc Diameter</b>                             | 125 mm                          |
| <b>Power Supply Cord</b>                                  | 2,5 m                           |
| <b>Vibration Uncertainty (K Factor), Disc Sanding</b>     | 1,5 m/s <sup>2</sup>            |
| <b>Product Dimensions (L x W x H):</b>                    | 289 x 139 x 103 mm              |
| <b>Max Output Power</b>                                   | 2000 W                          |
| <b>Vibration Uncertainty (K Factor), Surface Grinding</b> | 1,5 m/s <sup>2</sup>            |
| <b>Anti-Restart Function (NVR Switch)</b>                 | 1                               |
| <b>Sound Pressure Level</b>                               | 83 dB(A)                        |
| <b>Vibration Level, Disc Sanding</b>                      | ≤ 2,5 m/s <sup>2</sup>          |
| <b>Noise Uncertainty (K Factor)</b>                       | 3 dB(A)                         |
| <b>Weight Without Cable (EPTA)</b>                        | 2,3 kg                          |
| <b>Continuous Input Power</b>                             | 1200 W                          |
| <b>Tool Category</b>                                      | Grinding, Sanding and Polishing |
| <b>No load speed</b>                                      | 2800 - 12000 min <sup>-1</sup>  |
| <b>Spindle Thread</b>                                     | M14                             |
| <b>Sound Power Level (L<sub>WA</sub>)</b>                 | 94 dB(A)                        |

More info

<https://makita.ae/product/angle-grinder-9562cr/>