

Angle Grinder GA5040CZ



Product Description

1 400 W • 125 mm • 11 000 min⁻¹

Compact tool for cutting and grinding, with adjustable speed

A small but powerful 1 400 W angle grinder with a 125 mm wheel for demanding professional use. Constant speed electronics, excellent SJS2 anti-vibration technology and AVT anti-vibration side grip. Adjustable speed and tool-less wheel replacement.

Product Features

- ⊙ Double insulated
- ⊙ Rubberized soft grip for more comfort and control
- ⊙ Soft grip for increased operator comfort
- ⊙ Makita's patented Super Joint System protects the gearbox and operator from kickback.
- ⊙ Super Joint System (SJS) mechanical clutch system helps minimize motor and gear damage
- ⊙ Electronic current limiter helps protect the motor from overload
- ⊙ Anti-restart function prevents accidental start-up even if the tool is plugged to power source with the switch ON
- ⊙ Constant speed control minimizes reduction in rotation speed under load

Product Specifications

Power Supply Cord UK	2,5 m
Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	6,5 m/s ²
Grinding Disc Diameter	125 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	89 dB(A)
Vibration Level, Disc Sanding	2,5 m/s ²
Power Supply Cord	4,0 m
Continuous Input Power	1400 W
Product Dimensions (L x W x H):	303 x 140 x 116 mm
Sound Power Level (L _{WA})	97 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	2,5 - 3,6 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2100 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1

Tool Category	Grinding, Sanding and Polishing
No load speed	2800 - 11000 min ⁻¹

More info

<https://makita.ae/product/angle-grinder-ga5040cz/>