

Angle Grinder GA7050



Product Description

2 000 W • 180 mm • 8 500 min⁻¹

Efficient tool for cutting and grinding

An efficient angle grinder with an anti-restart function for demanding applications. 2 000 W motor and 180 mm wheel. Labyrinth channel construction protects the armature and the field coil from impurities in the cooling air.

Product Features

- ⊙ Compact and lightweight design
- ⊙ The labyrinth ducting of the engine compartment protects the engine from the impurities present in the cooling air.
- ⊙ The rubber grip on the handle ensures a good working grip
- ⊙ Side handle optionally left or right
- ⊙ Double insulated

Barcode

88381606011

Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	6,5 m/s ²
Max. Depth of Cut	49 mm
Grinding Disc Diameter	180 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	97 dB(A)
Vibration Level, Disc Sanding	4,0 m/s ²
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	432 x 200 x 132 mm
Continuous Input Power	2000 W
Sound Power Level (L_{WA})	105 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	4,5 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	3600 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Tool Category	Grinding, Sanding and Polishing
Dead Man's Switch (No Lock-On)	1
No load speed	8500 min ⁻¹

More info

<https://makita.ae/product/angle-grinder-ga7050/>