

## Angle grinder GA9040S



### Product Description

2 600 W • 230 mm • 6 600 min<sup>-1</sup>

#### 230 mm (9") 2,600 W Angle Grinder, Soft Start, Large Trigger Switch

An angle grinder for extra-heavy-duty professional use. A powerful 2 600 W angle grinder with a large 230 mm wheel for demanding applications that require high capacity. AVT anti-vibration side grip and tool-less wheel replacement. Back handle turns.

### Product Features

- ⊙ Externally accessible brushes for easy serviceability
- ⊙ Double insulated
- ⊙ Three position vibration absorbing side handle for increased comfort
- ⊙ Large rubber tool rest protects work piece from scratches
- ⊙ Electronic soft start feature for smooth start ups
- ⊙ Spiral bevel gears for smoother rotations, quieter gear noise and a more efficient transfer of energy
- ⊙ Ergonomically balanced for easy handling
- ⊙ Ergonomic and easy to use

### Product Specifications

<b>Power Supply Cord UK</b>	2,5 m
<b>Bore Size (Arbor Diameter)</b>	22,23 mm
<b>Vibration Level, Surface Grinding</b>	5,5 m/s <sup>2</sup>
<b>Max. Depth of Cut</b>	68 mm
<b>Grinding Disc Diameter</b>	230 mm
<b>Vibration Uncertainty (K Factor), Disc Sanding</b>	1,5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	93 dB(A)
<b>Vibration Level, Disc Sanding</b>	≤ 2,5 m/s <sup>2</sup>
<b>Power Supply Cord</b>	4,0 m
<b>Continuous Input Power</b>	2600 W
<b>Product Dimensions (L x W x H):</b>	503 x 250 x 140 mm
<b>Sound Power Level (L<sub>WA</sub>)</b>	101 dB(A)
<b>Spindle Thread</b>	M14
<b>Weight Without Cable (EPTA)</b>	6,4 - 8,9 kg
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max Output Power</b>	4900 W
<b>Vibration Uncertainty (K Factor), Surface Grinding</b>	1,5 m/s <sup>2</sup>
<b>Dead Man's Switch (No Lock-On)</b>	1
<b>Tool Category</b>	Grinding, Sanding and Polishing
<b>No load speed</b>	6600 min <sup>-1</sup>

More info

<https://makita.ae/product/angle-grinder-ga9040s/>