

# Angle Grinder LXT DGA455RFJ



### Product Description

18V LXT • 115 mm • 8 500 min<sup>-1</sup>

Powerful angle grinder with highly enhanced Brushless DC motor. Paddle type switch.

Powerful cordless angle grinder with 18V voltage. Standard angle grinder discs available. Slim body design for added comfort. Antirestart function. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

#### Product Features

 $\odot$  XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions

 ADT (Automatic torque Drive Technology): The speed is automatically regulated during operation in order to achieve optimum performance depending on the requirements

Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
 Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
 Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
 Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
 Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
 Active Feedback sensing Technology (AFT) stops
 Active Feedback sensing Technology
 Active Feedback sensing Technology
 Active Feedback sensing Technology
 Active Feedback sensing Technology
 Active Feedback
 Active

Battery protection system automatically shuts off power when the battery level is low

• Compact and lightweight design

#### **Product Specifications**

Bore Size (Arbor Diameter)	22,23 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	115 mm
Vibration Level, Surface Grinding	5,5 m/s²
Tool weight with battery (EPTA)	2,2 - 2,9 kg
Brushless Motor	YES
Battery Voltage	18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s²
Sound Pressure Level	83 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s²
Product Dimensions (L x W x H):	362 x 130 x 145 mm
Spindle Thread	M14
Sound Power Level (L <sub>wa</sub> )	91 dB(A)
Voltage LXT	1
Product net weight (new)	1,9 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Dead Man's Switch (No Lock-On)	1

Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s²
Anti-Restart Function (NVR Switch)	1
No load speed	8500 min <sup>-1</sup>

## Standard Equipment

● 1pc DC18RC Fast Charger

② 2pcs BL1830B (3.0Ah) 18V LXT Battery
 ③

Makpac Case

## More info

https://makita.ae/product/angle-grinder-lxt-dga455rfj/