

## Angle Grinder LXT

# DGA519Z



### Product Description

18V LXT • 125 mm • 3 000 - 8 500 min<sup>-1</sup>

**The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.**

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel. The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves. Tool only, battery and charger not included.

### Product Features

- Brushless maintenance-free and long-life motor
- disc brake
- Paddle switch
- Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381893510

### Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Max. Depth of Cut	29 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	125 mm
Vibration Level, Surface Grinding	7,0 m/s <sup>2</sup>
Tool weight with battery (EPTA)	2,5 - 3,1 kg
Brushless Motor	YES
Battery Voltage	18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s <sup>2</sup>
Sound Pressure Level	83 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s <sup>2</sup>
Product Dimensions (L x W x H):	396 x 140 x 147 mm
Sound Power Level (L <sub>WA</sub> )	91 dB(A)
Voltage LXT	1
Product net weight (new)	1,8 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
Max Output Power	660 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s <sup>2</sup>

Anti-Restart Function (NVR Switch)	1
No load speed	3000 - 8500 min <sup>-1</sup>

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga519z/>