

Angle Grinder LXT DGA519Z



Product Description

18V LXT • 125 mm • 3 000 - 8 500 min⁻¹

The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel. The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves. Tool only, battery and charger not included.

Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ disc brake
- ⊙ Paddle switch
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381893510

Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Max. Depth of Cut	29 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	125 mm
Vibration Level, Surface Grinding	7,0 m/s ²
Tool weight with battery (EPTA)	2,5 - 3,1 kg
Brushless Motor	YES
Battery Voltage	18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	83 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Product Dimensions (L x W x H):	396 x 140 x 147 mm
Sound Power Level (L_{WA})	91 dB(A)
Voltage LXT	1
Product net weight (new)	1,8 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
Max Output Power	660 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²

Anti-Restart Function (NVR Switch)	1
No load speed	3000 - 8500 min ⁻¹

Standard Equipment

- ⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga519z/>