

## Angle Grinder LXT DGA519Z



### Product Description

18V LXT • 125 mm • 3 000 - 8 500 min<sup>-1</sup>

**The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.**

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel. The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves. Tool only, battery and charger not included.

### Product Features

- ◎ Brushless maintenance-free and long-life motor
- ◎ disc brake
- ◎ Paddle switch
- ◎ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381893510

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	22,23 mm
<b>Max. Depth of Cut</b>	29 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Grinding Disc Diameter</b>	125 mm
<b>Vibration Level, Surface Grinding</b>	7,0 m/s <sup>2</sup>
<b>Tool weight with battery (EPTA)</b>	2,5 - 3,1 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	18 V
<b>Vibration Uncertainty (K Factor), Disc Sanding</b>	1,5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	83 dB(A)
<b>Vibration Level, Disc Sanding</b>	≤ 2,5 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	396 x 140 x 147 mm
<b>Sound Power Level (L<sub>WA</sub>)</b>	91 dB(A)
<b>Voltage LXT</b>	1
<b>Product net weight (new)</b>	1,8 kg
<b>System</b>	LXT 18V/36V
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Grinding, Sanding and Polishing
<b>Electronic brake</b>	1
<b>Dead Man's Switch (No Lock-On)</b>	1
<b>Max Output Power</b>	660 W
<b>Vibration Uncertainty (K Factor), Surface Grinding</b>	1,5 m/s <sup>2</sup>

<b>Anti-Restart Function (NVR Switch)</b>	1
<b>No load speed</b>	3000 - 8500 min <sup>-1</sup>

### Standard Equipment

◎ Sold without Battery or Charger

### More info

<https://makita.ae/product/angle-grinder-lxt-dga519z/>