

## Angle Grinder LXT DGA700ZK



### Product Description

36V (18Vx2) LXT • 180 mm • 7 800 min<sup>-1</sup>

**Efficient brushless tool with brake and safety switch underneath for high-capacity applications**

An efficient, high-capacity brushless angle grinder with a 180 mm wheel for demanding professional use. A high 18V+18V voltage is achieved with two 18V LXT batteries. Constant speed electronics, overload protection and wheel brake for added safety. Equipped with a safety switch underneath. Tool only, battery and charger not included.

### Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381850292

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	22,23 mm
<b>Max. Depth of Cut</b>	41 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Grinding Disc Diameter</b>	180 mm
<b>Vibration Level, Surface Grinding</b>	7,5 m/s <sup>2</sup>
<b>Tool weight with battery (EPTA)</b>	5,0 - 5,6 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	2 x 18 V
<b>Vibration Uncertainty (K Factor), Disc Sanding</b>	1,5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	91 dB(A)
<b>Vibration Level, Disc Sanding</b>	≤ 2,5 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	499 x 200 x 158 mm
<b>Spindle Thread</b>	M14
<b>Sound Power Level (L<sub>WA</sub>)</b>	99 dB(A)
<b>Voltage LXT</b>	1
<b>Product net weight (new)</b>	3,4 kg
<b>System</b>	LXT 18V/36V
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Grinding, Sanding and Polishing
<b>Electronic brake</b>	1
<b>Dead Man's Switch (No Lock-On)</b>	1
<b>Max Output Power</b>	1500 W
<b>Vibration Uncertainty (K Factor), Surface Grinding</b>	1,5 m/s <sup>2</sup>
<b>Anti-Restart Function (NVR Switch)</b>	1

**No load speed**

7800 min<sup>-1</sup>

Standard Equipment

⦿ With Carry Case and Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga700zk/>