

## Angle Grinder LXT

# DGA700ZK



### Product Description

36V (18Vx2) LXT • 180 mm • 7 800 min<sup>-1</sup>

**Efficient brushless tool with brake and safety switch underneath for high-capacity applications**

An efficient, high-capacity brushless angle grinder with a 180 mm wheel for demanding professional use. A high 18V+18V voltage is achieved with two 18V LXT batteries. Constant speed electronics, overload protection and wheel brake for added safety. Equipped with a safety switch underneath. Tool only, battery and charger not included.

### Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381850292

### Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Max. Depth of Cut	41 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	180 mm
Vibration Level, Surface Grinding	7,5 m/s <sup>2</sup>
Tool weight with battery (EPTA)	5,0 - 5,6 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s <sup>2</sup>
Sound Pressure Level	91 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s <sup>2</sup>
Product Dimensions (L x W x H):	499 x 200 x 158 mm
Spindle Thread	M14
Sound Power Level (L <sub>WA</sub> )	99 dB(A)
Voltage LXT	1
Product net weight (new)	3,4 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
Max Output Power	1500 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s <sup>2</sup>
Anti-Restart Function (NVR Switch)	1

No load speed	7800 min <sup>-1</sup>
---------------	------------------------

Standard Equipment

⦿ With Carry Case and Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga700zk/>