

Angle Grinder LXT DGA700ZK



Product Description

36V (18Vx2) LXT • 180 mm • 7 800 min⁻¹

Efficient brushless tool with brake and safety switch underneath for high-capacity applications

An efficient, high-capacity brushless angle grinder with a 180 mm wheel for demanding professional use. A high 18V+18V voltage is achieved with two 18V LXT batteries. Constant speed electronics, overload protection and wheel brake for added safety. Equipped with a safety switch underneath. Tool only, battery and charger not included.

Product Features

- Brushless maintenance-free and long-life motor
- Battery protection system automatically shuts off power when the battery level is low

Barcode

88381850292

Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Max. Depth of Cut	41 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	180 mm
Vibration Level, Surface Grinding	7,5 m/s ²
Tool weight with battery (EPTA)	5,0 - 5,6 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	91 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Product Dimensions (L x W x H):	499 x 200 x 158 mm
Spindle Thread	M14
Sound Power Level (L_{WA})	99 dB(A)
Voltage LXT	1
Product net weight (new)	3,4 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
Max Output Power	1500 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1

No load speed

7800 min⁻¹

Standard Equipment

◎ With Carry Case and Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga700zk/>