

Angle Grinder LXT DGA701ZKU



Product Description

36V (18Vx2) LXT • 180 mm • 7 800 min⁻¹

Efficient brushless tool with brake and safety switch underneath for high-capacity applications

An efficient, high-capacity brushless angle grinder with a 180 mm wheel for demanding professional use. A high 18V+18V voltage is achieved with two 18V LXT batteries. Constant speed electronics, overload protection and wheel brake for added safety. Equipped with a safety switch underneath. Tool only, battery and charger not included.

Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381867078

Product Specifications

| | |
|--|---------------------------------|
| Bore Size (Arbor Diameter) | 22,23 mm |
| Max. Depth of Cut | 41 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Grinding Disc Diameter | 180 mm |
| Vibration Level, Surface Grinding | 7,5 m/s ² |
| Tool weight with battery (EPTA) | 5,0 - 6,0 kg |
| Brushless Motor | YES |
| Battery Voltage | 2 x 18 V |
| Vibration Uncertainty (K Factor), Disc Sanding | 1,5 m/s ² |
| Sound Pressure Level | 91 dB(A) |
| Vibration Level, Disc Sanding | ≤ 2,5 m/s ² |
| Product Dimensions (L x W x H): | 499 x 200 x 158 mm |
| Spindle Thread | M14 |
| Sound Power Level (L _{WA}) | 99 dB(A) |
| Voltage LXT | 1 |
| Product net weight (new) | 3,4 kg |
| System | LXT 18V/36V |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Grinding, Sanding and Polishing |
| Electronic brake | 1 |
| Dead Man's Switch (No Lock-On) | 1 |
| Max Output Power | 1500 W |
| Vibration Uncertainty (K Factor), Surface Grinding | 1,5 m/s ² |
| Anti-Restart Function (NVR Switch) | 1 |

| | |
|----------------------|------------------------|
| AWS FUNCTION | YES |
| No load speed | 7800 min ⁻¹ |

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga701zku/>